

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List)

Black Diamond
40-80 and 30-60

*Note: Blank spaces are not permitted. If any item is not applicable, or no
information is available, the spaces must be marked to indicate that*

SECTION I

Manufacturer's Name

**Black Diamond Granules, Inc./Abrasive
Technologies, Inc.**

Emergency Telephone Number

651-436-6071

Address

**499 Cottage Grove Drive
Woodbury, MN 55129**

Telephone Number for Information

651-436-6071

Date Prepared: 3March 2008. Updated 8Dec08

Signature of Preparer (optional) *Janet L. Keyes, CIH*

SECTION II – Hazardous Ingredients/Identity Information

Hazardous components:

Black Diamond abrasives are stable, amorphous glass-like compounds.

Chemical identity	CAS #	Percent	OSHA PEL	ACGIH TLV
Coal slag	68476-96-0	99+ %	15 mg/m ³ (total) 5 mg/m ³ (respirable)	10 mg/m ³ (inhalable) 3 mg/m ³ (respirable)
Crystalline silica (quartz)	14808-60-7	*	0.1mg/m ³ (respirable)	0.05 mg/m ³ (respirable)

*Silica concentrations for 30-60 grade have been <1% and in 2006, 2007, and 2008 were below the detection level of 0.3%. Silica concentrations for 40-80 range from <0.4% to 1.6% in samples taken over the last six years (average = 0.9%).

SECTION III – Physical Characteristics

Boiling point	>>2500 °F	Specific gravity (H ₂ O = 1)	2.65
Vapor Pressure (mmHg)	N/A	Melting Point	2500 °F
Vapor Density (AIR =1)	N/A	Evaporation Rate (Butyl acetate=1)	N/A
Solubility in water	Negligible	Hardness	#7

Appearance and odor: **Black granular solid, no apparent odor**

SECTION IV – Fire and Explosion Hazard Data

Flash point (Method used) N/A Flammable limits: N/A

Extinguishing Media: none required

Special fire fighting procedures: None

Unusual Fire and Explosion Hazards: None

SECTION V – Reactivity Data

Stability Unstable Conditions to avoid

Stable **X** None

Incompatibility (Materials to Avoid): none known

Hazardous Decomposition or Byproducts: N/A

Hazardous Polymerization May Occur Conditions to Avoid

Will Not Occur **X** None

Section VI – Health Hazard Data			
Route(s) of Entry	Inhalation? Yes	Skin? Eyes, Yes	Ingestion? Not significant
Health Hazards (Acute and Chronic): May cause mechanical irritation to eyes and skin. Low toxicity by ingestion. Primarily hazardous by inhalation. Dust can cause mucous membrane irritation. Repeated or extremely high exposures to dust could cause pneumoconiosis.			
Carcinogenicity	NTP? No (yes for quartz)	IARC? No (yes for quartz)	OSHA Regulated No
Signs and Symptoms of Overexposure: Shortness of breath, coughing, impaired lung function			
Medical Conditions Generally Aggravated by Exposure: Respiratory illnesses			
Emergency and First Aid Procedures: Eyes: Flush with water for 15 minutes. Ingestion: Drink large amounts of water. Skin: wash with mild soap and water Inhalation: Move the person to fresh air; support breathing			
SECTION VII – Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled Follow established procedures for handling unregulated dusts and sands. Scoop or shovel into container, controlling dust. The material can be wetted with water to control dust. If material has been used for abrasive blasting, the waste material may be contaminated from the blasting.			
Waste Disposal Method: May be disposed of in an approved landfill in accordance with all EPA, state, and county disposal regulations. Disposal requirements may change once material has been used for abrasive blasting			
Precautions to be Taken in Handling and Storing Minimize inhalation and direct skin contact. Minimize dust generation. Respirator required in enclosed or poorly ventilated spaces and all other work involving high exposure.			
Other Precautions: Carefully follow all EPA, state, and county regulations			
SECTION VIII – Control Measures			
Respiratory Protection (<i>Specify Type</i>) NIOSH approved Type CE airline respirator for abrasive blasting. NIOSH approved disposable dust mask (N100 recommended) for comfort, protection against dust when pouring material			
Ventilation	Local Exhaust To maintain exposure below TLV/PEL	Special None	
	Mechanical (<i>General</i>) To maintain exposure below TLV/PEL	Other None	
Protective Gloves: Use gloves to prevent skin abrasion		Eye Protection Safety glasses or chemical goggles	
Other Protective Clothing or Equipment Safety glasses and normal work clothing for limited exposure. Type CE abrasive blasting respirator (including head and face protection) and sturdy coveralls to protect against high dust levels and abrasive effects when doing abrasive blasting			
Work/Hygienic Practices Normal practices.			
<i>The data in this material safety data sheet relate only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information is believed to be correct as of the date issued. Since the use of this information and the conditions of use of the product are not within the control of Black Diamond/Abrasive Technologies, it is the user's obligation to determine procedures for safe use and disposal of the product and to follow the appropriate safe procedures.</i>			